
CENTRO III



Full-wood Centro III NW centre-speaker complete the Classic Series , granting excellent results in voice reproduction as functional element in a multi-channel system together with Centro III NW or Ares.

Diapason Direct Drive technology is used for direct connection from the amplifier to the bass driver without the use of a low-pass filter in the crossover, giving grater transient speed in low frequency range. Drive units are made by the best manufacturers to strict Diapason specifications. Only materials which have been thoroughly tested are used, to ensure the best acoustic performance and to allow ease of driving by any kind of amplifier.

The high-pass crossover circuit is hard wired with Van den hul CS cable in oxygen-free silver coated copper, eliminating deleterious sonic effect of printed-circuit boards.

Metal black painted Wall Bracket C is available for wall fixing.



VIA FURA 40, 25125 BRESCIA - ITALY
TEL. +39 030 33840964 - INFO@DIAPASON-ITALIA.COM
WWW.DIAPASON-ITALIA.COM

CENTRO III



SPECIFICATIONS

Frequency response: 45/20.000 Hz

Bass driver: Ø 110 mm polymetylpentene Diapason Direct Drive

Tweeter: Ø 26 mm silk soft dome

Efficiency: 88 dB/1W/1m

Freq. crossover: 4.400 Hz

Nominal impedance: 6 Ohm

Min impedance: 3,3 Ohm/200 Hz

Type: posterior load reflex

Finish: walnut veneer wood

Weight per speaker: 9 Kgs

Dimensions speaker (W X D X H): 166x190x940 mm



VIA FURA 40, 25125 BRESCIA - ITALY
TEL. +39 030 33840964 - INFO@DIAPASON-ITALIA.COM
WWW.DIAPASON-ITALIA.COM